



FischerPanda 8000x PVMV-N



General Technical Data

Model	Panda 8000x PVMV-N
Generator Type	Compact Power
Generator Family	8000
Generator Version	PVMV-N
Article number	0013364
Area of Application	Vehicle (F)
Frequency	50
Generator manufacturer	Fischer Panda GmbH
Isolation class of windings	H
Nominal Speed	3000
Voltage Regulation	xControl /fpControl
Voltage Tolerance	±3V
Cos Pi	0.85

Electrical Alternator

Engine Speed	3000
Nominal Voltage in Volt	230
Frequency	50
Number of Phases	1
Nominal Performance	6.8
Nominal Performance	8,0
Continuous Performance	6.1
Continuous Performance	7.2

Engine

Engine Manufacturer	Kubota
Engine Type	KU Z482
No. Cylinders	2
Displacement	479
Starter System	On Request

Exhaust Emissions Standard

IMO MARPOL 73/78	x
------------------	---

Sound Insulation Capsule (Generator Housing)

Version	GFK 4DS
Sound Cover Type	GFK
Sound Insulation Material	4DS
Dimensions Housing L x W x H	870 x 515 x 634
Total Weight of Generator with Capsule	230
Sound levels [dB(A)] 7m / 5m /1m	52 / 62 / 67
Drawing Ref.	FP1-044753.pdf

Hose Diameters

Cooling water Hose	25.0 mm
Fuel Hose	8.0 mm
Exhaust Hose	40 mm

Service- / Installation Kits / Shock mountings

Service kit	0000693
Service Kit "Plus"	0006365
Shock-mounting, captive	0002752

